



ROAD PATCH NOTE:

FOR PAVEMENT REPAIR IN ROADWAYS UNDER THE ROAD CUT MORATORIUM (SWPWD STANDARDS CH. 3.2.16.A), THE MINIMUM MITIGATION FOR ALLOWED OPEN CUTS IS TO REPAVE HALF THE WIDTH OF THE PAVED SURFACE FOR A DISTANCE OF 100 FEET (50 FT EACH DIRECTION FROM THE CUT) UNLESS THE CUT CROSSES OVER THE CENTERLINE, WHICH WILL REQUIRE REPAVING THE FULL WIDTH OF THE PAVED SURFACE FOR A DISTANCE OF 100 FT.

OUTSIDE OF THE TRENCH REPAIR AREA, GRIND THE EXISTING HMA TO A DEPTH OF 1 1/2 INCHES. INLAY TO EXTEND ACROSS THE TRENCH PATCH AREA.

NOTES:

ALL CSTC AND CSBC SHALL COMPLY WITH WSDOT STANDARD SPECIFICATION 9-03.9(3).

ALL BACKFILL AND AGGREGATE SHALL BE COMPACTED TO 95% AND DENSITIES SHALL BE DETERMINED BY A MODIFIED PROCTOR (ASTM D1557). HMA DENSITIES SHALL BE DETERMINED AS PER THE WSDOT STANDARD SPECIFICATIONS.



PUBLIC WORKS
DEPARTMENT

ARTERIAL STREET TRENCH SURFACE RESTORATION DETAIL

DWG.
NO. 3-17B